

STROBE DRIVER

MS-230DA [for 15W single lamp]
PS-240D [for 60W single lamp]
PS-250D [for 120W single lamp]

Strobe driver series

Outstanding balance of brightness, functions, and operating abilities. Accompanied with wide variety of lamp houses, the series of multi-purpose stroboscope power supplies are suited to a wide range of motion analysis and image inspection applications.






Features





- Internal triggering
- External triggering
- Triggering by contact signal (optional cable needed)
- Triggering by power supply frequency
- X contact signal triggering (PS-240D and PS-250D) (optional cable needed)



■ Specifications





Model	MS-230DA	PS-240D	PS-250D
Flash Rate	60~26,500 r/min		
Input Signal	Electric signal : 3-5V _p , Pulse wave (POS. or NEG.) Contact signal : MAKE or BREAK		
Output Signal	3~5V _p , Pulse wave		
Power Supply	AC90~110 V, 50/60 Hz		
Flash Duration	6 μsec or less	40 μsec or less	50 μsec or less
Flash Tube Power	15 W max	60 W max	120 W max
Dimension (W×H×D)	270×170×190 mm	270×240×368 mm	270×240×518 mm
Weight	6.8 kg	15 kg	23 kg
			

■ Lamp houses compatible with the MS-230DA

Collective lens type	Collective lens type	Reflector type	Reflector type
SLA-154A	ML-230AS	SLA-154A	SLA-151A
			
(with 1A1-001)	(with 1A1-015)	(with 1A1-002)	

■ Lamp houses compatible with the PS-240D

■ Lamp houses compatible with the PS-250D

Reflector type	Wide reflector type	Reflector type	Wide reflector type
SLB-601	SLD-601	SLB-1201A	SLD-1201
			

Specifications are subject to change for improvement without a notice.

Xenon Flash / Torque Dynamometers / Bearing Inspection Systems

SUGAWARA Laboratories Inc.

8-2 Minami-Kurokawa, Asao-ku Kawasaki-shi, Kanagawa 215-0034 Japan

Phone: 81-44-989-7320 Fax: 81-44-989-7338

URL <http://www.sugawara-labs.co.jp/> E-mail info@sugawara-labs.co.jp

